



The **RWF** wall canopy



Innovative form and function

Robinhood RWF 900 Wall Canopy

○ A clever new angle

Get closer to the action with this smart innovation in rangehood design. The sloping front panel and slim design create increased working space while retaining a large surface extraction area.

○ High-performance slot extraction

The perimeter slots create a much higher air speed than conventional rangehoods. This means steam, grease and odours in the area are quickly whisked away.

○ Hidden micromesh filter

An easy-clean stainless surface keeps the single filter out of sight and directs steam and odours to perimeter slots. The multi-layered micromesh filter traps grease effectively - it's simple to remove and is easily maintained with a regular clean in the dishwasher.

○ Halogen down lights

Twin halogen lights, mounted in the front control section, provide clear illumination that's easy on the eye. Lamps are quick and easy to replace.

○ Three-speed extraction

The powerful centrifugal fan can be set to low, medium or high to match your cooking styles. Steam vegetables, stir-fry spices and sear steaks without thinking twice.

○ Recirculation if you can't duct

In situations where ducting isn't possible, this rangehood can be fitted with a charcoal filter that cleanses the air effectively before returning it to the kitchen.

○ Fingertip control

Modern soft-touch buttons make fan speed and lighting selection a breeze, so you can focus on your cooking.

○ Turns off if the worst happens

If you have a cooking disaster, and something catches fire, the rangehood automatically switches off to prevent flames and sparks being sucked into the ducting or ceiling.

Product incorporates a thermal overload function that senses extreme heat and disconnects power to the motor temporarily.



Extraction	Gross Airflow: Up to 1048m ³ per hour extraction power.* Net Airflow: Up to 870m ³ per hour extraction power. <small>*The airflow figures are calculated to the IEC61591 standard and includes a 10% tolerance due to motor performance variations.</small>
Finish	Stainless steel and glass.
Lighting	Halogen lighting.
Filter	Multi-layered micromesh. Dishwasher safe.
Decibel rating	Speed 1: 51.0 dB. Speed 2: 58.0 dB. Speed 3: 63.0 dB.
Ducting	Round 150mm ducting outlet. Recirculation option available.
Charcoal Filter Code	2615: 1 pack
Chimney Extensions	2613: 3048mm/10ft 2614: 3658mm/12ft
Safety	Automatic shut off if flames are detected. Fire retardant plastic parts.
Models	RWF3CH9G: 900 model
Dimensions	

See Wall Canopy Operation and Installation instructions on our website for further information on ducting and recirculation.

Due to ongoing research and development, the manufacturer reserves the right to change specifications without notice. If specifications are important to end use, please ask your merchant. Terms and conditions are subject to change without notice. Brochure issued January 2010.

New Zealand 0800 760 667 ○ www.robinhood.co.nz
Parbury Building Products (NZ) Limited

Australia 1800 648 556 ○ www.robinhood.com.au
Parbury Pty Limited ABN 63104298062

 Robinhood